

Technical Data Sheet

Version: 2.0

TITANOS R906 Rutile Titanium Dioxide Pigment

Description	R906 is a specially-purpose pigment used in all kinds of paints for high quality demand coating applications. It is sulfate process and provides an excellent opacity and easy dispersion.
Applications	<p>It is recommended for evaluation in:</p> <ul style="list-style-type: none"> • Architectural Paints. • Powder coating. • Industrial OEM/ Refinish paints. • Flexible ink. • 3C paints.
Typical Properties	<p>TiO₂ Content, %: ≥ 94 Rutile Content, %: ≥98 Brightness: ≥95 Oil Absorption(g/100g): ≤21 pH Value: 6.5-8.5 45 μm Residue (m/m), %: ≤0.01%</p>
Classifications	<p>ISO 591: R2 ASTM D-476-00: Type II CAS number: 13463-67-7 Color Index: 77891 Pigment white 6</p>
Storage	Keep the product un-stacked in dry and closed rooms at normal temperature and air humidity. To achieve best possible results, we recommend storage under the condition stated above and use within 12 months from delivery.
* Typical Properties not to be construed as specifications	

WWW.TITANOS.COM

Disclaimer:

The information given in this publication is obtained from sources believed to be reliable and every effort has been made to ensure that the data is correct and not misleading. However, Titanos accepts no responsibility for any errors, omissions or incorrect information or for any loss or consequential losses.